



Specifications Philips LED Panel  
SlimBlend RC400B 33W 3600lm - 840  
Cool White | 60x60cm - UGR <22 -  
Power Over Ethernet - MSE

[View Product](#)

General Information

|                          |                                                        |
|--------------------------|--------------------------------------------------------|
| SKU                      | 230424                                                 |
| EAN                      | 8718699177027                                          |
| Brand                    | Philips                                                |
| Manufacturer Name        | Philips SlimBlend RC400B LED36S/840 POE W60L60 VPC MSE |
| Any Lamp all-in warranty | 5 Years                                                |
| Average Lifetime (h)     | 70000                                                  |
| Series                   | RC400B                                                 |

Technical Information

|                             |                                |
|-----------------------------|--------------------------------|
| Technology                  | LED Integrated                 |
| Replaces (Watt)             | 4x18                           |
| Wattage                     | 33                             |
| Voltage (V)                 | 220-240                        |
| Dimmable                    | Dimmable with Philips Interact |
| Colour Code                 | 840 Cool White                 |
| Colour temperature (Kelvin) | 4000 Cool White                |
| Colour Rendering (Ra)       | 80-89                          |
| Colour of Light             | White                          |
| Light colour options        | Single Color                   |
| Luminous Flux (Lumen)       | 3600                           |

|                          |                               |
|--------------------------|-------------------------------|
| Luminous Efficacy (lm/W) | 109                           |
| Suitable for Outdoor     | No                            |
| IP-rating                | IP20                          |
| Impact Protection (IK)   | IK02 - 0.20 joule             |
| Fixture Connection       | PI [Push-in connector 3-pole] |
| Driver Included          | Yes                           |
| Power factor             | >0.95                         |
| Product Type Category    | LED Panel                     |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| Mounting Method       | Recessed                       |
| Unified Glare Rating  | < 22 - for general areas       |
| Optical Cover         | PMMA (Polymethyl methacrylate) |
| Operating Temperature | -10 to +40                     |
| Emergency Lighting    | No Emergency Unit              |
| Colour of the Fixture | White                          |
| Housing               | Steel                          |
| Colour of material    | White                          |

## Dimensions

|                |         |
|----------------|---------|
| LED panel size | 60x60cm |
| Length (mm)    | 595     |
| Width (mm)     | 595     |
| Height (mm)    | 52      |

## Why Any-lamp?



Order from the **largest lighting specialist** in Europe



**Customised** quotation

## Sensor Information



Up to **7 years warranty**



**Easy** return process

|                |           |
|----------------|-----------|
| Type of sensor | No Sensor |
|----------------|-----------|