



Specifications Noxion LED Panel Delta Pro V4 Aluminium/Metal White 29W 3700lm - 830 Warm White | 60x60cm - Emergency 1H - UGR <19

[View Product](#)

General Information

|                          |                                                                                                     |
|--------------------------|-----------------------------------------------------------------------------------------------------|
| SKU                      | 248851                                                                                              |
| EAN                      | 8719157048422                                                                                       |
| Brand                    | Noxion                                                                                              |
| Manufacturer Name        | Noxion LED Panel Delta Pro V4 29W 3700lm 3000K 1200*300 UGR<19 (2x36W eqv.) + Emergency integration |
| Any Lamp all-in warranty | 6 Years                                                                                             |
| Average Lifetime (h)     | 50000                                                                                               |
| Series                   | Delta Pro                                                                                           |

Technical Information

|                             |                 |
|-----------------------------|-----------------|
| Technology                  | LED Integrated  |
| Replaces (Watt)             | 4x18            |
| Wattage                     | 29              |
| Voltage (V)                 | 220-240         |
| Dimmable                    | Not Dimmable    |
| Colour Code                 | 830 Warm White  |
| Colour temperature (Kelvin) | 3000 Warm White |
| Colour Rendering (Ra)       | 80-89           |
| Colour of Light             | White           |
| Light colour options        | Single Color    |
| Luminous Flux (Lumen)       | 3700            |

|                          |                   |
|--------------------------|-------------------|
| Luminous Efficacy (lm/W) | 128               |
| IP-rating                | IP40/IP20         |
| Impact Protection (IK)   | IK02 - 0.20 joule |
| Fixture Connection       | Fast connector    |
| Finish of Reflector      | PET               |
| Power factor             | >0.90             |
| Product Type Category    | LED Panel         |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| Mounting Method       | Recessed                       |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PS (Polystyrene)               |
| Operating Temperature | -20 to +40                     |
| Emergency Lighting    | 1H Emergency Light             |
| Colour of the Fixture | White                          |
| Housing               | Aluminium, Metal               |
| Colour of material    | White                          |

## Dimensions

|                |         |
|----------------|---------|
| LED panel size | 60x60cm |
| Length (mm)    | 595     |
| Width (mm)     | 595     |
| Height (mm)    | 14      |

 **Sensor Information** Order from the **largest lighting specialist** in Europe  **Customised** quotation

Type of sensor



Up to **7 years warranty**

No Sensor



**Easy** return process